

22971

Rec PCT/PTO

24 FEB 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number  
WO 2004/019674 A1

- (51) International Patent Classification<sup>7</sup>: A01G 13/02 (74) Agent: ARGYRIADIS, Korinna; 14, Sina Street, GR-10672 Athens (GR).
- (21) International Application Number: PCT/GR2002/000047 (81) Designated States (*national*): AU, HU, MK, NZ, PL, SK, US, ZA.
- (22) International Filing Date: 29 August 2002 (29.08.2002) (84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR).
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant and (72) Inventor: DAIOS, Asterios [GR/GR]; 12th Km Veroia-Naousa, GR-59200 Naousa (GR).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: PLASTIC FILM FOR COVERAGE WITH LOOSE OPENINGS FOR WEIGHT INSERTION AT ITS EDGES



(57) Abstract: The invention refers to a plastic film for coverage with loose openings for weight insertion at its edges that is used in linear cultivations whose edges (3) have been elongated up to 100 % and have been folded and welded onto the main part of the plastic film with consecutive umbrella weldings (7). Due to the elongation of its edges (3) and the shape of the umbrella weldings (7), consecutive hoppers (8) are formed along the edge of the film. During the use of the film and due to the inclination that the film has towards its edges the hoppers (8) that form the loose openings for the fluid material in the weight insertion vaults (9) can readily accumulate any fluid material (11,12) and guide it by means of gravity to the weight vaults (9) where it is entrapped. Hence the weight insertion process becomes a rather simple matter without excessive cost and strenuous work.

WO 2004/019674 A1

BEST AVAILABLE COPY

**PLASTIC FILM FOR COVERAGE WITH LOOSE OPENINGS  
FOR WEIGHT INSERTION AT ITS EDGES**

*The invention refers to a plastic film for coverage with loose openings for weight insertion at its edges that is used in linear cultivations whose edges (3) have been elongated up to 100 % and have been folded and welded onto the main part of the plastic film with consecutive umbrella weldings (7). Due to the elongation of its edges (3) and the shape of the umbrella weldings (7), consecutive hopper shaped loose openings (8) are formed along the edge of the film. During the use of the film and due to the inclination that the film has towards its edges the hopper shaped loose openings (8) can readily accumulate any fluid material (11,12) and guide it by means of gravity to the weight vaults (9) where it is entrapped.*

*Several linear cultivations that are covered with plastic films in low tunnels (strawberries, watermelons, tomatoes etc) or with mulching films (asparagus) require cultivation works to be made while the cultivation line is covered with the film. The cultivation works are however hindered if the film is covered (buried) with soil along its edges. Several films have been developed that incorporate weight in pockets along their edges before or during their use which can be opened any time any cultivation work is required.*

*A high labour cost is required for the insertion of weight, that often reaches in monetary value the cost of the plastic film itself. This occurs because the soil is manually inserted at regular intervals in the pockets, through the openings that exist between the folding and the main body of the film. These openings are not distinct and are rather difficult to open for the user since they only open manually and very diligently because the sections of the plastic film between which these openings are formed cling together due to the fact that they are of the same length. In such a plastic film it is impossible to think of an easy way of filling the pockets with soil and in particular of thinking of a mechanised way of filling them.*

*Furthermore filling the film with a weight material is a strenuous and time consuming process and even worse these pockets have to be filled under adverse weather conditions and during a season (usually in winter) that there*

are scarce labour resources. As a result many farmers do not fill the pockets with enough weight. Hence the wind can easily lift the film, damaging it and leaving the cultivation line exposed.

This is the most important disadvantage of the hereto known plastic films  
5 that incorporate weight at their edges:

In the present invention an integrated and innovative solution is proposed, for a plastic film that easily incorporates weight along its edges - almost automatically - during its use without any excessive labour cost, by forming loose openings on these edges. Hence the use of the film becomes a  
10 lot easier and considerably more economical. The incorporated weight can be soil, sand or mud or a combination of them since they are materials that abound in the field and they do not add any further cost.

The invention takes advantage of the natural property of various fluids to flow to the lowest points due to gravity. Moreover it takes advantage of the fact  
15 that the plastic films for coverage of linear cultivations are positioned in such a manner that their lowest points are located along their edges. According to the invention, as it will be shown in detail further on, the edges of the film are formed in such a fashion that the flow of the soil or sand or the mud that falls on the plastic film is readily and uniformly guided to the aforementioned edges, at  
20 a low labour cost and are entrapped.

Figure 1 exhibits the application of the plastic film with loose openings for weight insertion at its edges on a linear cultivation under low tunnels

Figure 2 exhibits one way of materialising the invention and a detail of it and Figure 3 shows several forms of the "umbrella" welding.

25

One of the ways of materialising the invention is described below:

A thin and oblong plastic film (1) of any length (a) and width (b) ( $a \gg b$ ), is produced using any polyolefin or a combination of them in virgin or recycled state. The plastic film (1) can incorporate several additives, it can be  
30 transparent or it can have any colour in each of its surfaces.

The two edges (3) along the length of the plastic film are lengthways elongated forming a zone of width (c) (Figure 2 with detail) less than 15 cm and preferably approximately 5 cm. One way of achieving this elongation is by pretensioning the edges of the plastic film. The edges (3) of the plastic film are elongated to a value between 0 % and 100 % so that they finally acquire a nominal length value that is up to 100 % higher compared to the length of the rest of the film. The elongation can be uniform across the length of the film or local and repeated. Subsequently the pretensioned edges (3) of the plastic film are folded to the main body of the film to a width (d) up to 20 cm and preferably 10 – 15 cm. Hence every folded strip (5), that can be elongated in its whole ( $c = d$ ) or in a part of it ( $c < d$ ), is looser compared to the rest of the plastic film.

When the plastic film that has elongated edges and that it was wound in a role, is unwound, the edges are "separated" from the main body of the plastic film. This is due to the fact that the two superimposed parts of the plastic film are of different length (the elongated sections are looser compared to the rest of the plastic film).

The opposite is true with the normal plastic films where the lack of loose edges lead to having the edges stick to the main body of the plastic film.

Namely after the loose lengthways edges are created so that they easily open – separate – each folded stripe (5) is subsequently welded to the main body of the plastic film with consequent – lengthways – weldings (7) which have the "umbrella" shape. Between two subsequent umbrella weldings (7) of the main body of the plastic film and the elongated – loose – part (4) of the folded stripe (5), a hopper shaped loose opening is formed (8). Each hopper shaped loose openings (8) during the use of the film is readily opened, due to difference in length of the two superimposed parts of the film and the shape of the umbrella weldings. It is of paramount importance that the weldings have an umbrella shape since the hopper shaped loose openings (8) can only be formed in this manner - taking advantage of the loosen edge that aims at accumulating the fluid material.

The hopper shaped loose opening (8) is oblong and it could be considered similar to a boat without bottom.

Each umbrella welding (7) can have any shape contributing to the formation of the hopper shaped loose opening (8) and the weight vault (9). Such umbrella shapes can comprise linear or curved components or a combination of them. The umbrella weldings (7) can comprise only the "roof" (Figure 3, 7.1, 7.2, 7.3) or the "base" (Figure 3, 7.4, 7.5, 7.6) as well and they must be placed so that the tip of the roof points – preferably – towards the mid-section of the plastic film. The distance (e) of two consecutive umbrella weldings (7) can be of any value and preferably up to 50 cm, hence that would also be the length of the hopper (8). The umbrella welding (7) can stem from the crease (6) or at a small distance from it and end at the initial edge (3) of the plastic film or at a small distance from it.

The opening (10) through which the accumulated soil is inserted by means of gravity to each vault (9) that is simultaneously the bottom of the hopper shaped loose opening, is defined by the distance (e) between the two consecutive umbrella weldings (7) in combination with their dimensions. The construction is so that the length (x) of the opening (10) measured along the plastic film is preferably less than 20 cm.

At the weight vaults (9) small holes (2) can be made – preferably exactly below the edges of the roof of the welding – so that the excess water flows out of the film.

When the plastic film is unwound and applied on the field (Figure 1) the loose part (4) opens due to the different tension levels – or different length – forming a hopper shaped loose opening (8) – without any particular effort. During the application of the film, soil is either manually (e.g. by shoveling soil on the film) or by any mechanised means thrown on top of it. Most of the amount of the soil will be inserted through the hopper shaped loose openings hopper will slide into the weight insertion vaults (9) due to the inclination of the plastic film at its edges. The rest of the amount of the soil will be soaked by rain water (natural or artificial) and will be led as mud into the weight insertion vaults (9) providing the required weight whereas the water will finally leak through the holes (2) out of the plastic film.

**CLAIMS**

1. *Plastic film for coverage with loose openings for weight insertion at its edges (1) of any length (a) and width (b) where  $a \gg b$  with weight insertion vaults along its edges that is characterised by the fact that its edges (3) lengthways are elongated to a value of up to 100%, uniformly across its length or locally, and are folded and welded to the main body of the film with consecutive lengthways umbrella weldings (7.1 to 7.6) so that hopper shaped loose openings (8) are formed, for weight insertion into the weight storage vaults.*
2. *Plastic film for coverage with loose openings for weight insertion at its edges (1), according to claim 1, that is characterised by the fact that the elongated zone (4) at each of its edges (3) is 15 cm wide and preferably 0 - 5 cm whereas the folded stripe (5) that incorporates the elongated zone (4) is up to 20 cm wide and preferably 10 - 15 cm.*
3. *Plastic film for coverage with loose openings for weight insertion at its edges (1), according to claims 1 and 2 that is characterised by the fact that the consecutive umbrella shaped weldings (7.1 to 7.6) are at a distance (e) from each other preferably up to 100 cm and form a non-welded opening (10) along the plastic film of length (x) up to 20 cm.*
4. *Plastic film for coverage with loose openings for weight insertion at its edges (1), according to claims 1 - 3 that is characterised by the fact that the umbrella shaped welding (7) comprises only the roof that is of any shape (7.1, 7.2, 7.3) or comprises the base as well that is of any shape (7.4, 7.5, 7.6) and in such a manner that the roof as well as the base have any inclination with respect to the length of the plastic film, and preferably the tip of the roof points at the mid-section of the plastic film.*




figure 1





figure 3



# INTERNATIONAL SEARCH REPORT

International application No  
PCT/JP 02/00047

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A01G13/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 A01G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 295 00 393 U (BOECKENHOFF BERNHARD) 23 February 1995 (1995-02-23) page 5; figure 2	1-4
A	DE 299 19 489 U (ORBITA FILM GMBH) 17 February 2000 (2000-02-17) the whole document	1-4
A	DE 297 07 670 U (BOECKENHOFF BERNHARD) 3 July 1997 (1997-07-03)	
A	WO 00 62597 A (DAIOS ASTERIOS D) 26 October 2000 (2000-10-26)	
A	DE 200 19 622 U (EBERT REINHARD) 22 March 2001 (2001-03-22)	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

23 April 2003

Date of mailing of the international search report

02/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl  
Fax (+31-70) 340-3016

Authorized officer

De Lameillieure, D

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GR 02/00047

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 29500393	U	23-02-1995	DE 29500393 U1	23-02-1995
DE 29919489	U	17-02-2000	DE 29919489 U1	17-02-2000
DE 29707670	U	03-07-1997	DE 29707670 U1	03-07-1997
WO 0062597	A	26-10-2000	GR 99100128 A	29-12-2000
			CZ 20020677 A3	16-10-2002
			WO 0062597 A1	26-10-2000
			HU 0202507 A2	28-11-2002
			SK 2792002 A3	10-09-2002
DE 20019622	U	22-03-2001	DE 20019622 U1	22-03-2001
			DE 10006383 A1	23-05-2001
			EP 1101399 A2	23-05-2001